

NEW

Cryogenic Mill "IQ MILL-2075"

~ Intelligent Quick-Mill ~

Perfect for pretreatment of hard-to-grind polymers
- Specifically designed for grinding, agitating, and dispersing various samples -

In instrumental analysis of trace samples, fine grinding and thorough homogenization are critical to achieving high measurement reproducibility. Conventional grinding methods, however, often require long processing times of 10 minutes or longer, consume a large amount of liquid nitrogen, and generate substantial operating noise. The Cryogenic Mill "IQ MILL-2075" addresses these challenges with a compact, benchtop design that combines high speed, quiet operation and ease of use. In addition, its unique rapid reciprocating torsional motion* - enabled by a highly durable, high elasticity belt - delivers fast, quiet, and highly efficient grinding performance.

Compared with its predecessor, the "IQ MILL-2075" features a snap-lock mechanism for quick mounting and removal of sample containers, significantly enhancing workflow efficiency. *Japanese Patent No. 7064786

Smart quiet design



IQ MILL-2075

Features of IQ MILL-2075

1. Easy to use and simple to operate

● Snap-lock operation

Tool-free, snap-lock operation allows for smooth mounting and removal of sample containers, significantly improving workflow efficiency.



Sample grinding section

● Easy setup with rotary knob and touch panel

Required settings are only: grinding speed, grinding time, number of cycles, and waiting time. The settings can be easily done with the rotary knob and touch panel.



Maximum 10 sets of settings can be saved simply by entering in "FILE LIST".

2. Fast and efficient grinding

● Powerful impact and shear crushing capabilities bring significant reduction in grinding time

Rapid reciprocating torsional motion* enables sample grinding in a short period of time.

● Milling up to three samples at a time in the same program

Equipped with a holder that holds up to three sample containers for efficient grinding.

● Liquid nitrogen cooling kit for cryo-milling


The minimum liquid nitrogen consumption is only about 300 mL for energy saving. Room-temperature grinding without the use of refrigerants is also supported.

Polystyrene (20 pellets)

2000 rpm x 60 sec x 1 cycle

Pretreatment temperature

25 °C 0 °C -196 °C



3. Titanium sample containers are standard

● Titanium sample containers offering high chemical inertness are now standard

Synthetic/biopolymer grinding applications


Some of the grinding applications and a list of application examples are shown below.

Polyethylene (LDPE) 0.48 g

A hard-to-grind sample




3000 rpm x 30 sec
Cryogenic grinding
x 2 cycles




Electronic circuit board 2.1 g

A sample that can be ground
at room temperature



2500 rpm x 30 sec
Room temp. grinding
x 10 cycles




Bark of moso bamboo

Hard-to-grind sample



2000 rpm x 10 sec
Room temp. wet* grinding
x 2 cycles
* Buffer solution used



For more information, visit our website [here](#) or scan the QR.



Specifications

Grinding method	Cryogenic grinding, Room temperature dry grinding, Room temperature wet grinding	
Parameter settings	Rotation speed (rpm)	50 to 3000 (stepless)
	Rotation time (sec)	10 to 60 (10 sec steps)
	Inter-cycle pause time (sec)	0 to 600 (10 sec steps)
	Cycle count (number of repetitions)	1 to 20 (1 cycle step)
	Programmable parameters	Up to 10 sets of rotation time, inter-cycle pause time, and cycle count (number of repetitions) can be stored.
Safety function	Hazardous operation prevention by magnetic microswitch.	
Main unit dimensions and weight	Width 270 x Depth 340 x Height 300 (mm), 12 kg	
Power (50/60 Hz)	100/120 VAC or 200/240 VAC (450 VA)	
Standard accessories	Sample container, Insulation container, Insert tube, Cooling container, Tongs, Cooling holder, Sieve set, Grinding balls (Tungsten carbide and Zirconia), SS Grinding Rod 12 (Carbide stainless steel)	

* Noise level during grinding (a reference) : 55 dB (when grinding PS pellets with a 12 mm diameter zirconia grinding ball at a rotation speed of 3,000 rpm)



FRONTIER LABORATORIES LTD.

Visit our website for the latest information
www.frontier-lab.com